## ସ୍ଥ୍ୟତିସିପାଲ୍ <mark>ସହାବିଦ୍ୟାଳୟ, ରାଉ</mark>ରକେଲା MUNICIPAL COLLEGE, ROURKELA

DIST-SUNDARGARH ODISHA-769012

ACCREDITATED WITH B+ GRADE BY NAAC(2nd CYCLE-2016)

Email-municipalcollege8@gmail.com,website-www.municipalcollegerkl.com,Tel-0661-2501838

/MCR

### QUOTATIONS CALL NOTICE

Sealed quotations are invited from registered firms / Agency having valid GSTIN for supply of following items to Municipal College, Rourkela. The quotations must reach to the office of the undersigned by speed post/Regd Post /or by hand within seven days from date of issue this notice. The detail specification for each item is attached to this letter. Quotation is to be submitted strictly in conformity with the specification mentioned and the format given below.

SL No	Name of the item	Base Price per Unit	Taxes	Total cost per unit
1	Desktop computer	Oint		
2	UPS			
3	MFM Printer			
4	LED TV 65 inches			
5	Wireless Mice & Camera with MIC for virtual meeting			

NB: No of items to be supplied are : Desktop computer -12 nos ,UPS 12 nos ,MFM Printer- 02nos Led TV 65 Inches -01 no , Wireless Mice & Camera with MIC for virtual meeting -01 set .


#### TERMS AND CONDITIONS

- 01. Quotations must reach within the stipulated date after which it shall not be entertained under any circumstances.
- 02. Base price and applicable rate of tax and other incidental expenses, if, any, shall be expressed clearly in the quotation. Supply order time must be mentioned clearly.
- 03. The undersigned reserves the right to accept or reject any or all quotations without assigning any reason thereof.

Copy to: College Notice Board College website/Concerned file /Accounts Section/Office copy for record.

### Deectop Seperationing

Desktop	Specification	
Items		
Cabinet Form Factor	Specification Tower/Misso Tower/	
Chipset Number	Tower/Micro Tower (15.1 to 26 Litres)	
Processor Make	Intel H670/Intel® H770 or higher Chipset	
Processor		
Processor Generation	x86 64-bit architecture	
Processor Description	13 Or higher	
Processor Number	Intel Core i3 or higher	
Number of Cores and Threads per Processor	Intel Core i3 13100 or higher  Max Turbo Frequency 4.5Ghz, Minimum 4 Cores and 8 Threads or higher	
Operating System	- medas of higher	
RAM Size (GB)	Windows 11 Home Factory Preloaded	
RAM Expandability up to (using spare DIMM Slots in GB)	DDR-4 8GB 3200 (16 X1) or higher (2 DIIM Slots)	
Integrated Graphics	64 GB or higher	
Supported for discrete NVIDIA/AMD Graphics Card up to 6GB	Intel UHD Graphics 770 or higher Yes	
Type of Drives used to populate the Internal Bays		
Total HDD Capacity (GB)	NVMe SSD	
Total SSD Capacity (GB)	NA	
Optical Drive	512GB NVMe SSD	
Drive Bays	Optional Two 3.5" (2.5") HDD	
Slots for Upgradation	1 PCI Express 4.0 x16, 1 PCI Express 3.0 x1, 1 PCI (Full Height).	
AN	2 M.2 slots for WLAN & SSD	
Ports and Connectors	LAN: Integrated 10/100/1000M  Front: 1 headphone/microphone combo; 3 Super Speed USE SGbps signalling rate; 2 SuperSpeed USB 10 Gbps signalling rate; 1 USB Type-C, total 6nos USB in front for easy access Rear: 1 HDMI; 1 Serial Port; 1 line in; 1 line out; 1 power Connector; 1 No. 45 - 100 Connector; 1 N	
irmware Trusted Platform Module	connector; 1 RJ-45; 1 DP; 2 USB 2.0	
lardware Security lock slot	Security lock slot	
ower Supply	180-260Watt Internal power supply with minimum 90% efficiency	
ertification	Bidder should submit OEM bid specific authorization & the same authorization may be verified by the respective OEM if required.  OEM must have the ISO 9001,14001, ISO 20001, ISO 27001 Certificate  Microsoft Windows, Energy star 8.0 certified  Bidder should submit BIS, BEE, EPEAT, UL, ROHS Certificate of	
eyboard Mouse	products at the time of participation of the Bid.	
	USB Keyboard; USB Optical Mouse	
Ionitor	19.5" LED Display with CTO Certified and same must be belongs to the same OEM	
	3 Year Onsite Warranty	



### UPS SPECIALMION

		nteractive UPS Specifications	
SI. No.	Feature	General Specifications	
1	UPS Capacity (total)	600VA/360W	
5	input Voltage	230 VAC nominal	
3	Input Frequency	45 - 65 Hz	
4	Brownout Transfer	145 VAC typical	
5	Over-voltage Transfer	290 VAC typical	
6	Voltage on Battery	230 VAC typical (stepped approximated sine wave)	
7	Frequency - On Battery	50Hz typical	
8	Transfer Time	@50 Hz : 6 ms typical, 10 ms max	
9	Air Ventilation	Should have Side and Back Honey bee Perforation for hea dispersion	
10	Protection from Humidity & Dust	UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity	
11	Battery Saver Option	UPS Should have Battery Saver Option to increase the life of th Battery upto 5 years	
12	No Load Shutdown	UPS Should work on loads of 2-3 watts also	
13	AC Surge Protection	Full time, 160 joules	
14	Automatic Re start of UPS	In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference.	
15	Type (maintenance-free)	12V, 7.2 Ah	
16	Typical recharge time	4- 6 hours	
17	Operating Temperature	0°C to 40°C	
18	Storage Temperature	-15°C to 45°C	
19	3 power outlets	With battery backup and surge protection	
20	Power Cord	1.2 meters	
21	Runtime for Single PC load (60W ± 15W)	27 min (normal mode)	
22	Runtime for Workstation PC (100W ±15W)	13 min (normal mode)	
23	Battery Saver (to save on battery life)	Thru toggle button on front panel	
_	Certification	BIS	
$\overline{}$	Designed and Manufactured in India	Yes	
26	Warranty	2 yeasrs	

Municipal College Rourkela - 12

### MFM PRINTER

### SPREIFICATION Paye-1

	Generic
Description of Stores	Multifunction Machine Printer with Minimum 1 Year On Site Warranty, including Cartridge and Power Cord/Adapter
Core Function	Print, Scan and Copy
Print Technology	Laser
Cartridge Technology	Composite Cartridge
Type of Printing	Monochrome (Black)
RAM Size (MB)	256
Storage Capacity (in GB)	0
Features	Fax
Operating System Compatibility	Windows 10 and Above, Linux, Mac OS, Windows Server
	Printing
Print Paper Size	A4 and Legal
Minimum Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Monochrome (Black) (in PPM)	26 to 30
Minimum Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Colour (in PPM)	Not Applicable
Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size- Mono (in PPM)	Not Applicable
Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size- Color (In PPM)	Not Applicable
Auto Duplexing Printing/Coping (2-sided Feature)	Yes
	Scanning
Maximum Scan Area (Platen/Flatbed Size)	A4 and Legal
A4 Scan Speed -Colour (Image Per Minute) @ 300 x 300 dpi	11 to 20
Scan To Functions	Email
A4 Scan Speed - Mono (Image Per Minute) @ 300 x 300 dpi	11 to 20
	COPYING
Reduction and Enlargement	Yes

# MFM PRINTER SPOREN FICATION

Pase-2

200	PAPER HANDLING
Original Document Feeder Type (For Scanning and Copying)	Automatic Document Feeders (ADF)
Feeder Capacity (Number of Sheets) (For Scanning and Copying)	31 to 40
Number of Main Paper Tray	1
Total Paper Tray Combined Capacity (Number) at 75 GSM	101 to 200
Bypass Tray Facility	No
If Yes, Bypass Tray Capacity	0
Connectivity	
Connectivity	USB Port,Ethernet Port,Wi-Fi
Accessories Provided	USB Cable
	Performance
Minimum Yield of the Cartridge/Ink/Toner supplied with Machine as per IS/ISO/IEC: 19752/2017 for Black (Number of Prints)	700
Minimum Yield of the Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints)	0
Minimum Duty Cycle (Number of Prints/Month)	10,001 to 20,000
	POWER
Power Supply	Single Phase AC 220 - 240 V, 50 - 60 Hz
Maximum Power Consumption (in Watt)	1300
Environmental	
Minimum Operating Temperature (Degree C)	10
Maximum Operating Temperature (Degree C)	30

Municipal College Rourkela - 12

## SPREIFICATION Page-3

Minimum Operating Humidity (%RH)	20	
Maximum Operating Humidity (%RH)	80	
	Dimension	-
Standard Machine Weight with Single Tray (in Kg)	11	
	Certification	
BIS CRS Compliance	Yes as per IS 13252 (Part 1)	
Maximum Number of Prints covered under Product warranty (Whichever is earlier)	30000	
EPR Registration in respect of the manufacturer/authorised importer as per E waste rules as amended up to date	Yes	
Agreed to Provide a copy of EPR Registration Certificate to the Buyer on Demand	Yes	

TV. Deuthicahon Pare-1

	Screen Size	65
	Brightness (cd/m²)	350Nits or better
	Contrast Ratio	1200:1
	Dynamic Contrast Ratio	400,000:1
General Features	Response Time (ms)	8.0
The same of the same	Display resolution (H x V, pixels)	3840 × 2160
THE SHEET AND	HDR (High Dynamic Range) compatiblity	Yes (HDR10, HLG)
	Aspect Ratio	16:9
	Portrait/Tilt Compatibility	Yes
	Dimming type	Frame Dimming
	Display Device	LCD
	Panel Type	IPS
	Backlight type	
Display features	Color gamut (NTSC)	Direct LED
	Operation time	69%
	Haze (%)	16/7
	Viewing Angle (Right/Left)	1%
		178 (89/89) degree
OR ALL SHARES AND A SECOND	Viewing Angle (Up/Down)	178 (89/89) degree
	HDMI Signal	4096 x 2160p (24, 50, 60 Hz 3840 x 2160p (24, 25, 30, 5i 60 Hz), 1080p (30, 50, 60 Hz 1080/24p, 1080i (50, 60 Hz), 720p (30, 50, 60 Hz), 720/24p, 576p, 576i 480p,480i
Audio Specs	Speaker Position	Down Firing
	Audio Power Output	10W + 10W
Professional	Prosettings	Yes (Simple Pro settings men
features	HDMI auto wake-up	Yes
	Operating System	Android TV
	On-board Storage (GB)	16GB
	RAM	3GB
Network Specs	Wi-Fi Certified	Yes
	Wireless LAN	Integrated
	USB playback codecs	MPEG1:MPEG1/MPEG2 PS:MPEG2/MPEG2 WEBM:AV1/AC4/ogg/AAC
Convenience	On Screen Clock	Yes
features	Sleep Timer	Yes
	On/Off Timer	Yes
The second second	Chromecast built-in	Yes
	Apple AirPlay	Yes
	IP Control	Yes
Control Specs	RS-232C Control	Yes
	HDMI-CEC	Yes
	HDCP	HDCP2.3 (for HDMI1/2/3)
	Composite Video Input (s)	1 (Side, Mini jack)

## TV 800 Specification Page 2

Inputs and outputs	HDMI inputs total	No. Teach
	Analog Audio Input (s) (Total)	3 (3Side)
	Digital Audio Output (s)	1 (Side Analog Conversion)
21	USB ports	1 (Side)
Doring to a	Ethernet inputs	2 (Side)
Design features	VESA* Hole Pitch (W x H)	1 (Side)
	Rated Power Consumption	300 x 300 mm
Environment Specs	Power Consumption (in Standby)	226W
	Dynamic Backlight Control	0.5 W
	Power Saving Mode / Back Light Off Mode	Yes
	Dimension of TV without Stand (W x H x D)	Yes
Measurements	Dimension of TV with Stand (W x H x D)	1462 x 842 x 71 mm
	Dimension of Package Carton (W x H x D)	1462 x 912 x 338 mm
	Weight of TV without Stand	1588 x 965 x 184 mm
Weight	Weight of TV with Stand	20.4 kg
245	Weight of Package Carton (Gross)	21.3 kg
	Carton (Gross)	28 kg



🔞 Offers GSI Benefits Become a Seller Bulk Order (AQs 🎵 Track Order 🌢



Employ 88 Industrybuying

@ BAR DIKON

Search Products by the sky calegory brand atc

a Login



Home / IT Security / Computer Accessories / WEBCAM / Logitech Master Series Graphite M. Bu ships within 5 days

#24,779 (Incl. of all taxes) \$20,999 - 18% OLT

UEP #94.995 0.86%.OFF

Logitech Master Series Graphite MX Brio 4K Ultra Hd Web Camera, 960-001548

Visit the Log tech Store

Get up to \$4,000° on a min. order value of \$5,498

Get up to \$3,600° on a min order value of \$5,498

PERMEN BRAND

view Offers

EMI starts at \$2202/month. No Cost EMI available EMI options

#### **Bulk quantity Discounts!!**

price per Select Quantity piece(incl of all tomes)

6-7

0

0 4-5 #2374053

0 8-more 223 500 93 F73,34119

£23 980 14

-

Quantity-1

#### ADD TO CART

BUY NOW

0 21

0

FEATURES

AVAILABLE OFFERS

XDEDE

Country of Origin

Switzerland USB-C to USB-C

Connectivity

First-time dat users only, T&C apply

First-time B28 users only 1&C opply

Advanced Autolocus

Focus Type

Package Contains

More WEBCAM products

More Logitech WEBCAM products

MX Brio, Mount Clip with Removable with Removable Adapter, USB-C to C 3.0 Cable, User Documentation

### O Check Delivery Details

Enter Program

Check

PRLPAID

Available

PART COD

Unavailable

COD

Available Return

period ?

### SPECIFICATIONS

### DESCRIPTION

Country of Origin Connectivity

Focus Type

Package Contains

Microphone Type

Width

Type of Product Part No

Weight Lens Type

image Sensor

**Switzerland** 

USB-C to USB-C Cable

**Advanced Autolocus** 

MX Bno, Mount Clip with Removable Adapter, USS-C to C 3 0 Coble, User Documentation

**Dual Beamforming** 

96 mm

4s Digital Zoom Web Camera

MOTOR OFFI 44 mm

137 g Gioss USB 30 Graphite

4K/30 tps, 1080p/80 tps 85 MF Sony STARVIS 960-001548











